Line Interactive UPS



BPI650 / BPI1000 / BPI1500 / BPI2200

BPI Series

THE MOST RELIABLE WITH AUTOMATIC VOLTAGE REGULATION



Application:

- Home and Home Office
- Small Office

Features:

- Overload Protection
- EMI, RFI, Surge and Spike Protection
- Phone / Fax / Modem / DSL / Network Protection (Optional)
- USB Connectivity Port (Optional)
- LED Status Indicator
- Fire-resistant Capability
- Battery Management Technology
- Compact size
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave output
- Off-mode charging
- Cold start function
- Generator compatible

BPI650 BPI1000 BPI1500 BPI2200



► Technical Specifications of BPI Series

MODEL	BPI650	BPI1000	BPI1500	BPI2200	
CAPACITY	650VA / 360W	1000VA / 600W	1500VA / 900W	2200VA / 1200W	
INPUT					
Voltage	110/120V AC or 220/230/240V AC				
Voltage Range	81-145V AC / 162-290V AC				
Frequency Range	60/50 Hz (Auto Sensing)				
ОИТРИТ					
Voltage	110/120V AC or 220/230/240V AC				
AC Voltage Regulation	±10% (Battery Mode)				
Frequency Range		60 Hz or 50 Hz ± 1 Hz (Battery Mode)			
Transfer Time	Typical 2-6 ms				
Waveform (Batt. Mode)	Simulated Sine-wave				
BATTERY					
Battery Type & Number	12V/7AH x 1	12V/7AH x 2	12V/9AH x 2	12V/9AH x 2	
Typical Recharge Time	4-6 Hours recover to 90%				
INDICATOR					
AC Mode	Green Lighting	Green lighting			
Battery Mode	Green Flashing	Yellow flashing			
Fault	N/A	Red lighting			
ALARM		1			
Battery Mode	Sounding every 10 Sec				
Low Battery	Sounding every Sec				
Overload	Sounding every 0.5 Sec				
Fault	Continuously Sounding				
PROTECTION					
Full Protection	Overload, Discharge and Overcharge Protection				
Physical Size - UPS Module					
Dimensions (DxWxH) (mm)	279x101x142	320x130x182			
Weight (Kg.)	4.2	8.2	10.4	11	
Environmental					
Humidity	0 ~ 90% RH @ 0 ~ 40°C (Non-condensing)				
Noise Leval	Less than 40dB				
Certifications					
CE	Yes				
	Yes				

^{*}Specifications are subject to change without prior notice.




► Sockets Available

IEC Socket And Power Cord


Universal Socket With Power Cord

Schuko + IEC Socket With Power Cord












Model No.: BPI1000








Model No.: BPI1500







Model No.: BPI2200

